



| | |
|------------------|------------|
| Document code | B36 |
| Revision code | 01 |
| Revision date | 20.11.2014 |
| Publication date | 22.07.2014 |
| Page no | 1 |

PNEUMATIC MACHINE FOR HIND LEGS



USAGE AREA: 1ST CLASS SLAUGHTER HOUSES

QUALITY: ST 37, GALVANIZED BODY

PROPERTIES OF MACHINE

A-SUBJECT:

Providing pneumatic machine for hind legs for using in the slaughter hall of slaughter houses.

B- TECHNICAL PROPERTIES:

- Opens two back legs of the animal before the carcass dividing process and helps carcass dividing. Mounted on the monorail.
- Immobilize one of the leg with pneumatic piston and opens the other leg with the help of pneumatic cylinder and provide the needed gap.
- Kit body will be completely hot-dip galvanized.
- 63x1000 pneumatic cylinder will be used for joint-ground-crotch connection.
- 40x100 pneumatic cylinder will be used for joint-ground-crotch connection.
- 80x40 2 piece of polyethylen
- Diameter 14 length 100
- Air pump (10) for piston connection
- Midle stage valve

C. GENERAL ISSUES

- Will be appropriate to the matters which is signified on Technical Properties.
- 2 years of warranty will be provided for pneumatic machine for hind legs