



# PROFESSIONAL PNEUMATIC DENIDING MACHINE

**USAGE AREA** : 1<sup>ST</sup> CLASS SLAUGHTER HOUSES

**QUALITY** : STEEL

**CLASS** : PROFESSIONAL

**PROPERTIES OF MACHINE**



## A. SUBJECT

Used for HYDRAULIC DENIDING MACHINE of bovine

## B. TECHNICAL PROPERTIES:

- It will be capable of hydraulic system and swim 40 cattle grains per hour.
- The leather spinning machine will be powered by 4 HP power, 27 rpm endless screw motor reducer.
- In the skinning machine, the control button will be fixed or movable on the platforms.
- The leather swimming machine will be complex 304 quality stainless steel.
- The skinning machine will swim from the top to the bottom.
- Two 100x100 4 mm box profiles and 4500 mm length skids will be carried and a 120x120 4 mm box profile skin swimming boat and tanbur will be moved up and down.
- The total height of the machine will be 4500 mm.
- The range of motion will be from 350 mm to 1700 mm in the vertical axis.
- On both sides of the leather swimming machine there will be special twisted butcher working platforms 1000x840 mm wide. These platforms will have a steel pipe with a diameter of 42 mm and a guardrail height of 700 mm. These platforms will be positioned facing the cattle processing line at an angle of 23 degrees.
- The hydraulic system will provide platform motion.

## C. GENERAL ISSUES

- Will be appropriate to the matters which is signified on Technical Properties.
- 2 years of warranty will be provided for professional DENIDING machine.